

VERTICAL AIR CURTAIN (SELF CONTAINED)

	Model	Cu. Ft.	# of Shelves	HP	Amps	Crated Weight	Cabinet Dimensions		
							L	D	H
NEW	TAC-30	25.5	4	1/2	12.8	355	30	30 ¹ / ₈	80 ⁵ / ₈
NEW	TAC-36 ‡	31.3	4	3/4	7.5	420	36	30 ¹ / ₈	80 ⁵ / ₈
	TAC-48 ‡	34.0	4	1	12.0	490	48	30 ¹ / ₈	80 ⁵ / ₈
NEW	TAC-72 ‡	65.9	8	(2) 3/4	13.7	N/A	72	30 ¹ / ₈	81 ³ / ₄

Black vinyl exterior available at no extra charge.

Stainless steel exterior available (upcharge applies).

‡ TAC-36 & TAC-48 require 208-230/60 Hz, single phase, NEMA 6-15R.

TAC-72 requires 208-230/60 Hz, single phase, NEMA 6-20R.

VERTICAL AIR CURTAIN, GLASS SIDED (SELF CONTAINED)

	Model	Cu. Ft.	# of Shelves	HP	Amps	Crated Weight	Cabinet Dimensions		
							L	D	H
NEW	TAC-14GS	16.2	3	1/2	10.9	280	30 ¹ / ₄	30 ³ / ₈	56 ³ / ₈
NEW	TAC-30GS	25.5	4	1/2	14.3	N/A	30 ³ / ₈	29 ³ / ₄	80 ³ / ₄
	TAC-48GS ‡	34.0	4	1	12.0	475	48	30 ¹ / ₄	80 ⁵ / ₈

Black vinyl exterior available at no extra charge.

Stainless steel exterior available (upcharge applies).

‡ Requires 208-230/60 Hz, single phase, NEMA 6-15R.



TAC-48



TAC-48GS



TAC-30GS



TAC-30
(shown with black exterior and optional black aluminum interior)



TAC-14GS
(shown with black exterior)

Recommended Operating Conditions
• Units should not be installed near HVAC vents, fans or doorways that will disrupt the air curtain and compromise the function of the cabinet.
• Units should not be installed in direct sunlight.
• Air curtain models will run most efficiently when completely loaded with product.
• TAC models are designed to operate in an environment where temperature & humidity do not exceed 75°F and 55% respectively.
• Please be advised Air Curtain models are substantially louder than standard refrigeration models.

New Cantilever Shelving Available.
(TAC-72 standard with cantilever shelving)



Cantilever Shelving

FEATURES/BENEFITS

- Oversized environmentally friendly (R404A) refrigeration - holds 33°F to 38°F, the ideal temperature for fresh salads, sandwiches, desserts and beverages.
- Exterior - non-peel or chip white laminated vinyl, durable and permanent.
- Interior - attractive, NSF approved, white aluminum with 300 series stainless steel floor and deck pans. Available with black aluminum interior (upcharge applies); standard with black shelves.
- Designed for convenient access, fast service, and attractive display.
- Safety shielded fluorescent interior lighting for longer, brighter, shadow-free illumination.
- Adjustable, heavy duty, PVC coated wire shelves - 10 mil thick, pure grade vinyl coating (TAC-72 standard with two white cantilever shelves per level).
- Exclusive reversing condenser fan motor.
- Foamed-in-place polyurethane high density cell insulation (CFC free).
- Leg levelers standard.
- Self-contained system.
- Illuminated sign panel.
- Available with optional 2¹/₂" diameter castors (excludes remote models).
- See our website www.truemfg.com for the latest color & sign offerings.
- Optional black interiors available. Upcharge and lead times will apply.
- Optional stainless exteriors available. Upcharge and lead times will apply.

Remote cabinets available 14% off list (condensing units supplied by others; system comes standard with 404A expansion valve and requires R404A refrigerant). Consult factory technical service dept. for BTU information.