

REACH-IN SOLID DOOR REFRIGERATORS



TG1R-2HS

Model	Swing Doors	Cu. Ft.	HP	Amps	Crated Weight	Cabinet Dimensions L D H*		
SOLID DOORS								
TG1R-1S	1	31	1/3	8.5	370	29	34 ³ / ₄	78 ¹ / ₄
TG2R-2S	2	56	1/2	10.0	650	51 ³ / ₈	34 ³ / ₄	78 ¹ / ₄
TG3R-3S	3	85	1/2	11.8	770	76 ¹ / ₂	34 ³ / ₄	78 ¹ / ₄
SOLID HALF DOORS								
TG1R-2HS	2	31	1/3	8.5	390	29	34 ³ / ₄	78 ¹ / ₄
TG2R-4HS	4	56	1/2	10.0	650	51 ³ / ₈	34 ³ / ₄	78 ¹ / ₄
TG3R-6HS	6	85	1/2	11.8	770	76 ¹ / ₂	34 ³ / ₄	78 ¹ / ₄

* Height does not include 5" for castor height or 6" for optional legs.

* Height does not include 1" for system mechanical components.

Deep reach-in's provide greater depth to accept full sized pans.



TG3R-3S



TG2R-2S

FEATURES/BENEFITS

- Shelving - (3) heavy duty, PVC coated wire shelves per section (4) different interior kits available.
- Oversized and balanced, environmentally friendly, refrigeration system, factory sealed and pre-lubricated for long life.
- Food safe refrigerators hold 33°F to 38°F.
- 300 series stainless steel doors and rain-shield (the finest stainless available).
- Anodized quality aluminum sides, bottom and back.
- Interior - attractive, NSF approved, white aluminum sides and back. 300 series stainless floor and door liner.
- Foamed-in-place polyurethane high density cell insulation (CFC free).
- Lifetime guaranteed recessed door handles.
- Door locks standard.
- Exterior, digital temperature display.
- Positive seal self-closing doors with 120 degree stay open feature. Lifetime guaranteed door hinges.
- Incandescent interior lighting.
- 4" diameter swivel castors standard equipment. 6" legs available.
- Hot gas condensate for energy efficiency.
- Top mounted unit positioned out of food zone to maximize storage capacity.
- Refrigerator models feature glass condensate pan to prevent electrolysis.
- Self-contained system.

Curb mountable units for TR, TA & TG series only. (5% list upcharge)

Remote cabinets available 14% off list (condensing units supplied by others; system comes standard with 404A expansion valve and requires R404A refrigerant). Consult factory technical service dept. for BTU information.