

REACH-IN GLASS DOOR REFRIGERATORS

Model	Swing Doors	Cu. Ft.	HP	Amps	Crated Weight	Cabinet Dimensions L Dt H*
GLASS DOORS						
TG1R-1G	1	31	1/3	9.0	410	29 x 34 ⁷ / ₈ x 78 ¹ / ₄
TG2R-2G	2	56	1/2	11.4	710	51 ³ / ₈ x 34 ⁷ / ₈ x 78 ¹ / ₄
TG3R-3G	3	85	3/4	13.6	867	76 ¹ / ₂ x 34 ⁷ / ₈ x 78 ¹ / ₄
GLASS HALF DOORS						
TG1R-2HG	2	31	1/3	9.0	465	29 x 34 ⁷ / ₈ x 78 ¹ / ₄
TG2R-4HG	4	56	1/2	11.4	660	51 ³ / ₈ x 34 ⁷ / ₈ x 78 ¹ / ₄
COMBINATION HALF DOORS						
TG1R-1HG/1HS	2	31	1/3	9.0	465	29 x 34 ⁷ / ₈ x 78 ¹ / ₄
TG2R-2HG/2HS	4	56	1/2	10.0	640	51 ³ / ₈ x 34 ⁷ / ₈ x 78 ¹ / ₄

† Depth does not include 1³/₈" for door handle (glass door models only).

* Height does not include 5" for castor height or 6" for optional legs.

* Height does not include 1" for system mechanical components.



TG1R-2HG

Cabinets shown with various tray slide options



TG2R-2HG/2HS

FEATURES/BENEFITS

- Shelving - (3) heavy duty, PVC coated wire shelves per section (4) different interior kits available.
- Oversized and balanced, environmentally friendly, refrigeration system, factory sealed and pre-lubricated for long life.
- Food safe refrigerators hold 33°F to 38°F.
- Fluorescent interior lighting.
- 300 series stainless steel solid doors and rain-shield (the finest stainless available).
- Anodized quality aluminum sides, bottom and back.
- Interior - attractive, NSF approved, white aluminum sides and back. 300 series stainless floor and solid door liner.
- Positive seal self-closing doors with 120 degree stay open feature. Lifetime guaranteed door hinges.
- Foamed-in-place polyurethane high density cell insulation (CFC free).
- Energy efficient, "Low-E", thermal insulated glass on glass doors.
- Exterior, digital temperature display.
- Lifetime guaranteed recessed handles on solid doors.
- Door locks standard.
- Extruded, aluminum door frames on glass doors.
- Top mounted unit positioned out of food zone to maximize storage capacity.
- 4" diameter swivel castors standard equipment. 6" legs available.
- Refrigerator models feature glass condensate pan to prevent electrolysis.
- Hot gas condensate for energy efficiency.
- Self-contained system.

Curb mountable units for TR, TA & TG series only. (5% list upcharge)

Remote cabinets available 14% off list (condensing units supplied by others; system comes standard with 404A expansion valve and requires R404A refrigerant). Consult factory technical service dept. for BTU information.